

Material Safety Data Sheet

No. of Substance Safety Information :	06
Version:	B01
Compile Date:	2021-06-03

1. Information of substance and manufacturer:

Substance name:	Cu-Sn-Ni-Si-Zn Alloy		
Code:	boway42300		
Chemical name:	Cu-Sn-Ni-Si-Zn Alloy		
Category:	Metal compound		
Name of manufacturer/supplier	Ningbo Boway Alloy Material Co.,Ltd		
Address of manufacturer/supplier	No. 288, Honggang Road, economic development zone, Ningbo, China		
Telephone of manufacturer/supplier	86-574-89016105	Fax:	86-574-89016087
Website of manufacturer/supplier	http://www.bowayalloy.com/		
Emergency contact Tel:	86-574-89016105		

2. Component information:

Componen	Chemical name	Content (%)	CAS No.
Copper	Cu	87-91	7440-50-8
Tin	Sn	0.5-1.5	7440-31-5
Nickel	Ni	0.5-1.5	7440-02-0
Silicon	Si	0.1-0.3	7440-21-3
Zinc	Zn	remainder	7440-66-6
Co+Fe+Mg+P+Mn+Al		≤0.5	/

3、 Danger information

Warning:

Long time exposure to powder or smog of this product can lead to hurt on eyes, respiratory system and cortex, so protective items must be used, including goggle, appropriate cloth, necessary whole-body protection. After contact with it, a complete cleaning of the contacted body part must be done.

Note: this product is not dangerous in solid state, but dangerous in powder or smog state.

Category name:	Cu-Sn-Ni-Si-Zn Alloy
Danger information:	Metal powder or smog is irritative to skin and eyes, and hazardous to lung, but metal finish product itself is not hazardous.
Danger level (powder or smog):	Health: 1; Flammability:0 (0 is lowest level, 4 is highest level) Substance hazard: no

4、First aid measures:

For hazard by powder and smog

Contacted with eyes:	Clean with water inside eyelids for at least 15 minutes. In case that eyes feel uncomfortable, go to hospital immediately.
Swallowed:	Drink lots of water to promote emesis and go to hospital immediately.
Contacted with skin:	Clean with water.
Inhaled:	Take a rest in a well-ventilated and cool place, keep warm with cloth. If it's serious, go to hospital.

5、Fire and explosion information

Flammability information

explosibility	no
flammability	no
combustibility	no
flash	not applicable
natural burn	not applicable

Fire extinguishing agent

Extinguishing method: cover extinguishing agent on product surface
--

Anti- fire suggestion

Powder may lead to explosion or generate flammable gas.

6、Leakage treatment

In processing this product, powder may be generated and cause fire, so source of ignition must be removed. Only powder can lead to leakage, so sucking device must be installed to filter powder in the air and lower the concentration of powder.	
Leakage to air	not applicable
Leakage to water	not applicable
Leakage to ground	not applicable

7、Access, storage and transportation

Precautions for access

<p>Be careful when accessing and getting the product because the ends of product are easy to cut skin.</p> <p>It's easy to generate powder during machining, so protections must be used for eyes, skin and breathing.</p> <p>Pay attention to prevent the powder from leaking into air.</p> <p>Risk of product being turned over exists, which can cause crush, so be careful during handling.</p> <p>The end of strapping strip is possible to bounce and cut body, skin and eyes.</p> <p>Powder on clothes or tools should be cleaned and removed with water or vacuum cleaner, not through patting or other ways.</p>

Conditions for storage

Max. temperature for storage in store: no
Avoid storing in moist or acid or alkaline environment.

8、Exposure and protection:

Cu exposure standard	OSHA (PEL)		ACGIH (TLV)	
	ppm	Mg/m ³	ppm	Mg/m ³
	smog	no	0.1	no
powder	no	1	no	1
Sn exposure standard:	OSHA(PEL)		ACGIH(TLV)	
	ppm	Mg/m ³	ppm	Mg/m ³
	powder	no	no	no
Respiratory protection	Respiratory protection tools are needed and mask certified by NIOSH should be worn in case of long-time exposure to powder and smog.			
Ventilation protection	If powder and smog are possible to be generated in work, ventilation device and dust collection device must be installed, and eating and smoking is not allowed during work.			
Eyes and skin protection	Wear goggle, protective gloves to avoid being cut.			
Body protection	Wear appropriate clothes and safety shoes during work.			

9、Physical and chemical nature:

appearance	Solid metal with orange yellow
Melting point	1059°C
Boiling point	no
Specific gravity	8.75g/cm ³
Vapour pressure	Not applicable
Solubility	Not applicable
Ph value under 25°C	Not applicable

10、Safety and reactivity

inactive/inert substance

11、Toxicity

Source

Powder: swallowed, contacted with skin, inhaled, contacted with eyes
Smog: inhaled, contacted with eyes and skin
The product itself is not toxic.

Toxicity: this alloy product has no toxicity.

The toxicity of the single element is as follows (only for reference):

Corrosion to skin: no information

Irritation (to eyes, skin): copper product can cause contact dermatitis, and zinc is hazardous to eyes.

Acute toxicity: swallowing of copper powder by mistake can cause acute toxicity with symptoms such as emesis, powerlessness and stomachache. Inhaling too much powder can cause chest pain, fever, etc.

Powder and smog can aggravate asthma and emphysema patients' condition.

12、 Ecology information

The finish product has no toxicity to ecology.

Decomposability: no information

Accumulation: no information

Burstiness: no records indicate that the product will cause burstiness.

Toxicity of fish: some record shows that when the concentration of copper in water (especially soft water) is up to 0.015~3.0mg/l, it's toxic to many kinds of fish, crustacean animals, mollusk animals and plankton.

13、 Waste disposal

The waste of this product is not hazardous. When it's necessary to be discarded, send it to recyclers for recycling.

14、 Shipment and transportation

During shipment and transportation, direct contact with water is not allowed. It's possible that the product could fall down and turn over.

15、 Laws and regulations

Normally there's no specific law and regulation, but when in place where powder could be generated, work safety and health regulations must be followed.

16、 Other information

This MSDS information must be fully understood and accepted by all users and people who ship or store it or are exposed to it, and should be applied to regulations related to use, processing, manufacturing and management of this product. The latest information may be included here when compiling this MSDS document, but there's no guarantee to any content here.